



USER MANUAL



TEATRO DUE 650/1000

Table of contents

1.	Safety instructions	3
2.	Lamp.....	4
3.	Colour filters.....	4
4.	Installation.....	4
5.	Maintenance	4
6.	Technical data	5

1. Safety instructions

FOR SAFE AND EFFICIENT OPERATION

Be careful with heat and extreme temperature. Avoid exposing it to direct rays of the sun or near a heating appliance.

Not put it in a temperature bellow 41°F /5°C, or exceeding 95°F /35°C.

Keep away from humidity, water and dust.

Do not place the set in a location with high humidity or lots of dust.

Containers with water should not be placed on the set.

Keep away from sources of hum and noise such as transformer motor, tuner, TV set and amplifier.

To avoid placing on un-stable location select a level and stable location to avoid vibration.

Do not use chemicals or volatile liquids for cleaning.

Use a clean dry cloth to wipe off the dust, or a wet soft cloth for stubborn dirt.

If out of work, contact sales agency immediately.

Any troubles arose, remove the power plug soon, and contact with an engineer for repairing, do not open the cabinet by yourself, it might result a danger of electric shock.

Take care with the power cable.

Never pull the power cable to remove the plug from the receptacle, be sure to hold the plug. When not using the player for an extended period of time be sure to disconnect the plug from the receptacle.

2. Lamp

Disconnect the fixture from the mains.

To exchange the lamp please drive back the mandrel. After that please open the top part of the housing. Now exchange the lamp against one of the same type.

Please don't touch the lamp with your bare fingers.

Fitting lamps are: GX 9,5 650W , GX 9,5 1000W

3. Colour filters

It is strongly recommend ended you use only high temperature color filters (gel) in polycarbonate or similar specifications material.

4. Installation

This product is fitted with a suspension stirrup rotating around the body of the product ,thus allowing the product to be installed suspending or standing .The stirrup is fitted with a \varnothing 12mm clear hole for the attachment of a hook clamp or a stand pivot. Make sure the structure you are fixing the product to can stand the product load.

5. Maintenance

To ensure maximum performance of the product, a regular maintenance service should be carried out . Please make sure the product is cold and disconnected from power supply when doing this.

Clean all reflective parts such as reflector and lense (if fitted), opening the product, if necessary.

Check the lamp, the protection shields and the lenses (if fitted) and replace any visibly damaged component .

Clean air ducts and fans (if fitted) in order to allow proper ventilation activity on the product.

Check internal and external wiring and replace any cable which should be damaged by heat damaged component .

6. Technical data

Voltage	AC 230V / 50 Hz
Measurements	255 x 240 x 390mm
Weight	6kg

IMPORTER

B&K LUMITEC

2 rue Alfred Kastler
Zone Industrielle
67850 Herrlisheim - France

+33 (0) 3.88.96.80.90

+33 (0) 3.88.96.48.46

hello@bklumitec.com

www.bklumitec.com

